

## ■ L 型焊接变位机 *L type Welding Positioner*

### 功能描述 / Function Description

1. 主要用于不规则工件的定位，可根据客户的不同需求进行设计。
2. 可180度翻转。（可选）
3. 可升降，升降行程取决于客户要求。（可选）
4. 可360度回转，回转速度可调。

1. Mainly used for work piece with irregular shape, like Framework of car, loading machine, digger machine. We will design according to customers' requirement.
2. With function of 180tilting. (optional)
3. with function of lifting. Lifting stoke depends on customers' requirement. (Optional)
4. With function of 360 rotating. The rotating speed could be fixed speed or adjustable.



### 技术参数 / Technical Parameters

规格 Model	额定承载量 Loading Capacity (kg)	回转速度 Rotary Speed (rpm)	翻转速度 Tilting Speed (rpm)	回转角度 Rotation Angle (°)	翻转角度 Tilting Angle (°)	升降速度 Lifting Speed (mm/min)	最大重心距 Max Gravity (mm)	最大偏心距 Max Eccentricity (mm)	台面尺寸 Worktable Dia. (mm)
HBL-10	1000	0.05-0.5	0.5	n x ±360°	±180°	600	200	200	700
HBL-30	3000	0.05-0.5	0.3	n x ±360°	±180°	600	300	200	800
HBL-50	5000	0.05-0.5	0.2	n x ±360°	±180°	600	300	200	1000
HBL-70	7000	0.05-0.5	0.2	n x ±360°	±180°	500	300	200	1000
HBL-100	10000	0.05-0.5	0.2	n x ±360°	±180°	500	400	200	1200

## ■ L 型焊接变位机 *L type Welding Positioner*



> L型变位机 / L type positioner



> L型变位机 / L type positioner



> L型升降变位机 / L type elevating positioner



> L型变位机使用中 / Using of L type positioner



> L型变位机 / L type positioner



> 工程机械用L型变位机20T / L type positioner 20T